



SMART TRADING ASIA (PVT) LTD

Lot No. 3, Maithree Mawatha, Industrial Estate, Ekala, Ja-Ela, Sri Lanka.

Tele: 011 4 324 280 | 011 4 324 281 | Hotline: 077 0 034 200-4 | Fax: 011 2 225 835

E-mail: smarttradingasia@gmail.com

STEEL STRAPPING – DATA SHEETS

Blue Oiled Steel Strapping

Blue Oiled Steel Strapping is to heat treatment the steels at about 200 degree centigrade and make the steel surface to form a layer of dense ferroferric oxide film. Its main ingredient is ferroferric oxide.

The layer of protective film can prevent iron rusts, before packing, you also can paint a layer of anti-rust oil to prolong the store time. (Dense ferroferric oxide film can film the steel body isolated from air and water, and have the effect of anti rust) In general, they are 3-4 layer of packaging, or we can according to customer requirements for packaging.

Surface finish: Blue & Oiled

Material: /Q235B

Specification:

- Thickness: 0.5mm-0.8mm
- Width: 16-19mm

Elongation:

- High quality steel strip: 6%-10%

Tolerance:

- Thickness tolerance: 0.02mm
- Width tolerance: 0.1mm

Tensile strength:

- High quality steel strip: 850-980Mpa

Enwind type: Ribbon wound

Package: Hessian / cloth/iron pallet, etc





SMART TRADING ASIA (PVT) LTD

Lot No. 3, Maithree Mawatha, Industrial Estate, Ekala, Ja-Ela, Sri Lanka.
Tele: 011 4 324 280 | 011 4 324 281 | Hotline: 077 0 034 200-4 | Fax: 011 2 225 835
E-mail: smarttradingasia@gmail.com

Black Painted Waxed Steel Strapping

Painted packing steel strapping, black color. The surface is painted and waxed, which is a high-end product. It is durable and rust-proof. It has a high tensile strength, divided into machine packaging strapping and manual packaging strapping. It can make your product packaging more durable and beautiful. It is very flexible and diverse, we can customize the product details according to your requirements.

Surface finish: Black & Waxed

Material: Q235 B

Specification:

- Width:16MM -19MM

Elongation: 3%-10%

Tolerance:

- Thickness tolerance:0.02mm
- Width tolerance:0.1mm

Tensile strength:

- High quality steel strip:850-980Mpa

Enwind type: Ribbon wound



Product Name	Hoop Iron
Material	Q235B
Standard	GB/T 13912-2002, ISO 1464, JIS H8641, BS 729:1971, ASTM A123-1989
Tolerance	+/-0.02mm
Surface Treatment	Cold rolled steel strip
Width and Thickness	Width: 16-19 mm Thickness: 0.5-.8mm
Packaging	Hessian ,pallet;
Process	Rolling→Annealing→ Dip Coating→Straightening→Crop→Coiling
Applications	Packing, Industry and Constrution etc